

**BOROUGH OF HILLSDALE
ORDINANCE NO. 14-17
(Adoption)**

**AN ORDINANCE TO AMEND, REVISE AND SUPPLEMENT
CHAPTER 260 OF THE HILLSDALE BOROUGH CODE,
ENTITLED "STREETS AND SIDEWALKS" MOST NOTABLY,
SECTION 260-16, ENTITLED "STREET OPENING
REGULATIONS" WITH THE ADDITION OF SECTION 260-16.1
ENTITLED "SPECIFICATIONS AND PROCEDURES FOR
PAVEMENT"**

BE IT ORDAINED by the Borough Council of the Borough of Hillsdale, County of Bergen, that the Hillsdale Borough Code is hereby amended, revised and supplemented as to Chapter 260, entitled "Streets and Sidewalks", most notably Section 260-16, entitled "Street Opening Regulations" with the addition of Section 260-16.1, entitled "Specifications and procedures for pavement" as follows:

§ 260-16.1 Specifications and procedures for pavement.

The following specifications and procedures shall be applicable to all pavement on roads and streets within the Borough of Hillsdale:

- A. For openings of less than one hundred (100) square feet in surface area, the upper seven and one-half (7 ½) inches of trench shall be filled by the applicant with graded one-and-one-half-inch (1 ½) stone equal to the applicable and current State Specification(s), with dust, compacted by a five-ton roller. After twenty-four (24) hours of traffic, or other period as stipulated by the appropriate Borough official, the edges of the trench shall be saw cut parallel to the street center line and six (6) inches outside the widest trench limits, after which the upper three and one-half (3 ½) inches of stone shall be removed and final pavement shall be constructed. After thirty (30) calendar days, and after six (6) months, the applicant shall place fine aggregate bituminous concrete in depressed areas to form a smooth, even street surface.
- B. For openings of greater than one hundred (100) square feet in surface area, the upper seven and one-half (7 ½) inches of trench shall be filled by the applicant with five (5) inches of graded one-and-one-half-inch (1 ½) stone equal to the applicable and current State Specification(s), with dust, and one and one-half (1 ½) inches of stabilized base material equal to the applicable and current State Specification(s), compacted by a ten-ton roller. The surface shall be maintained by the applicant for not less than thirty (30) calendar days and, at the discretion of the appropriate Borough official, to a maximum of ninety (90) calendar days, such that maximum surface depression is one (1) inch. Thereafter, the edges of the trench shall be saw cut parallel to the street center line and six (6) inches outside the widest trench limits, after which the upper three and one-half (3 ½) inches of material shall be removed, and final pavement shall be constructed. After six (6) months, the applicant shall place fine aggregate bituminous concrete in depressed areas to form a smooth, even, street surface.


- C. For emergency openings from November 15 through March 31, the procedure shall be the same as for openings greater than one hundred (100) square feet, except that temporary paving material may be approved cold patching compound, if hot material is not available.
- D. Final pavement in all cases shall be four (4) inches of graded one-and-one-half-inch (1 ½) stone, equal to the applicable and current State Specification(s), with dust, two (2) inches of stabilized base material equal to the applicable and current State Specification(s), one and one-half (1 ½) inches of fine aggregate bituminous concrete equal to the applicable and current State Specification(s), feathered over a twelve-inch (12) width of tack coat, to meet adjacent surfaces. All thickness shall be as measured after compaction by a ten-ton roller.
- E. Where a trench exceeds one hundred (100) feet in length, a one-and-one-half-inch (1 ½) surface course shall be placed from curb to curb on all streets. Where a trench exceeds six (6) feet in width, or is skewed to street center line or is connected to spur trenches, a one-and-one-half-inch (1 ½) surface course shall be placed from curb to curb. In all cases the surface shall be cleaned end tack coat placed before application of surface course, which shall be feathered toward each curb.
- F. Upon prior approval of the appropriate Borough official, subgrade stone may be replaced with an equivalent thickness of stabilized base material.
- G. The roadway restoration and trench repair as stipulated within this ordinance shall be followed. If it is found during trench excavation that a roadway section is thicker than stipulated within this ordinance, the existing, thicker pavement section shall be constructed.
- H. All roadway restoration work shall be performed to maintain current drainage patterns. In addition, unless authorized by the Borough, roadway surface grade elevations shall not change. If milling is necessary to satisfy these requirements, milling shall be performed in accordance with current NJDOT regulation and in accordance with the requirements as stipulate by the Borough and its professionals.

NOW THEREFORE, BE IT FURTHER ORDAINED that this Ordinance, if adopted by the Borough Council shall, within five (5) days after its passage, Sundays excepted, be presented to the Mayor and Borough Clerk. The Mayor shall, within ten (10) days after receiving the ordinance, Sundays excepted, either approve this Ordinance by affixing his signature thereto or return it to the Council by delivering it to the Borough Clerk together with a statement setting forth his objections thereto or any item or part thereof. This Ordinance or any item or part thereof shall not take effect without the Mayor's approval, unless the Mayor fails to return this Ordinance to the Borough Council, as prescribed above, or unless the Borough Council, upon consideration of this Ordinance following its return shall, by a vote of two thirds (2/3rds) of all of the members of the Borough Council, resolve to override the veto.

Council member	Motion	Second	Yes	No	Absent	Abstain	Recuse
DeGise, Jason			x				
Frank, Douglas			x				
Kelley, Thomas	x		x				
Looes, Chrisoula			x				
Meyerson, Lawrence		x	x				
Pizzella, Frank			x				

Adopted: December 9, 2014

Attest: 
 Susan Witkowski
 Municipal Clerk


 Max Arnowitz
 Mayor